#### WORLD INTELLECTUAL PROPERTY ORGANIZ International Bureau



### INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51)	International	Patent	Classification	5	:

G06F 15/66

(11) International Publication Number:

WO 92/03800

A1

(43) International Publication Date:

5 March 1992 (05.03.92)

(21) International Application Number:

PCT/SE91/00530

(22) International Filing Date:

12 August 1991 (12.08.91)

(30) Priority data:

9002645-1

15 August 1990 (15.08.90)

SE

(71) Applicant (for all designated States except US): TELEVER-KET [SE/SE]; S-123 86 Farsta (SE).

(72) Inventor; and

- (75) Inventor/Applicant (for US only): BRUSEWITZ, Harald [SE/SE]; Televerket, S-123 86 Farsta (SE).
- (74) Agents: HOLMQVIST, Lars, J., H. et al.; Lars Holmqvist Patentbyrå AB, P.O. Box 4289, S-203 14 Malmö 4 (SE).

(81) Designated States: AT (European patent), BE (European patent), CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent), US.

#### Published

With international search report. In English translation (filed in Swedish).


(54) Title: METHOD OF MOVING A PIXEL A SUBPIXEL DISTANCE

$$(i, j)$$
  $(-1, -1)$   $(0, -1)$   $(1, -1)$ 

$$(0, -1)$$

$$(1, -1)$$

(-1, 0)



#### (57) Abstract

The invention relates to a method of moving a pixel a subpixel distance and is intended to be applied in picture coding methods to determine the value of a pixel located between the fixed pixels on the screen. The pixel value is calculated using a known motion vector and the pixel values located in the vicinity of the corresponding pixel in the previous picture. According to the invention at least 3x3 pixels from the previous picture are used and the pixel value is calculated as a sum of the previous pixel values weighted by coefficients depending of the motion vector. The coefficients are preferrably calculated as polynomials of the subpixel part of the motion vector.

## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

				•	
AT	Austria	ES	Spain	MĞ	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon -	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	អប	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic	SE	Sweden
CH	Switzerland		of Korea	SN	Senegal
CI	Côte d'Ivoire	KR	Republic of Korea	SU+	Soviet Union
CM	Cameroon	LI	Liechtenstein	TD .	Chad
cs	Czechoslovakia	LK	Sri Lanka	TG	Togo
DE*	Germany	LU	Luxembourg	US	United States of America
DK	Denmark	MC	Monaco		

<sup>+</sup> Any designation of "SU" has effect in the Russian Federation. It is not yet known whether any such designation has effect in other States of the former Soviet Union.

WO 92/03800 PCT/SE91/00530

5

## TITLE OF INVENTION: METHOD OF MOVING A PIXEL A SUBPIXEL DISTANCE

10

#### FIELD OF THE INVENTION

The present invention relates to a method of moving a pixel a subpixel distance. Subpixel distance refers to a distance shorter than the distance between two adjacent pixels (pixel = picture element). The inversion is intended to be applied in the picture coding methods for determining the value of a pix—located between the fixed pixels on the screen. This situation may occur in moving pictures where the pixels are moved arbitrary distances and thus, may end up between defined positions. The situation may also occur in conversion between different picture formats, so-called standard conversion.

#### STATE OF THE ART

According to the prior art usually 2x2 filters with socalled bilinear interpolation are used. The drawback with this technique is that it provides blurry pictures, especially in positions between two pixels. The reason is that the 2x2 filter has strong low- s characteristics.

30 This drawback is overcome to a great extent with the invention utilizing 3x3-filters or greater.

4x4 filters are also previously known, however, not with functions for calculating coefficients of arbitrary positions but only for half pixel distances. However, the present invention provides a method for arbitrary pixel distances.

#### SUMMARY OF THE INVENTION

40 Thus, the present invention provides a method of moving

a pixel a subpixel distance, wherein the value of the pixel is calculated using a known motion vector and values of pixels located in the vicinity of the corresponding pixel in the previous picture. According to the invention at least 3x3 pixels from the previous picture are used and the pixel value is calculated as a sum of the previous pixel values weighted by coefficients depending on the motion vector. The coefficients are calculated as functions of the subpixel part of the motion vector, preferrably as polynomials. Further features of the invention are set forth in the accompanying claims.

The invention will now be described in detail referring to the enclosed drawings.

## 15 BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1. is a diagram illustrating a 3x3 filter in accordance with the present invention.

Figure 2. is a diagram illustrating a 4x4 filter in accordance with the present invention.

20

25

30

10

## DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The purpose of the present invention is to assign a value to a pixel which is to be calculated from the previous picture. It is assumed that a vector indicating the position in the old picture corresponding to the actual pixel is available. This situation occurs for instance in picture coding with prediction and standard conversion between different picture formats.

In figure 1, the positions of nine pixels in the previous picture are shown as dots and the pixel of which the value is to be calculated, is marked with a circle. Thus, in the new picture the circle corresponds to pixel in a fixed barpattern, similar to the nine dots. The motion vector (not shown) may be of arbitrary length. In calculating the new pixel value the integer parts of the motion vector are not used but only the fractional parts from the centre pixel, in the figure denoted by f and g for respective directions. For both f and g -1/2 < f  $\leq$  1/2 and -1/2 <  $g \leq$  1/2. In accordance with the invention the pixel value q is calculated as

15

$$q(n,k) = \sum_{i=-1}^{1} \sum_{j=-1}^{1} a_{i}r_{j}p(n+x+i,k+y+j)$$

where al and rj are the filter coefficients,

5 n, k are the coordinates in the new picture, x+f, y+g is the motion vector, x and y being the integer part and f and g being the fractional part, p is the pixel value in the previous picture.

Thus, referring to figure 1, the pixel value of the 10 pixel at the left top should be multiplied with  $a_{-1}$  and  $r_{-1}$  et cetera.

The problem is separable horisontally and vertically meaning that the coefficient  $a_i r_j$  is a product of two coefficients  $a_i$  and  $r_j$ . The following coefficients for a 3x3-filter has been found:

$$a_{-1} = \frac{-2f + 3f^2 - |f^3|}{4}$$

$$a_0 = \frac{2 - 3f^2 + |f^3|}{2}$$

$$a_1 = \frac{2f + 3f^2 - |f^3|}{4}$$

25 and  $r_j$  are identical functions of g.

In figure 2 the corresponding situation of a 4x4 filter is illustrated. For f and g  $0 \le f < 1$  and  $0 \le g < 1$ . For a 4x4 filter in accordance with the invention the following coefficients are obtained:

$$a_{-1} = \frac{-7f + 12f^2 - 5f^3}{15}$$

$$a_0 = \frac{15 - 3f - 27f^2 + 15f^3}{15}$$

$$a_1 = \frac{12f + 18f^2 - 15f^3}{15}$$

$$a_2 = \frac{-2f - 3f^2 + 5f^3}{15}$$

5 and r<sub>j</sub> are identical functions of g.

The greater filter is chosen, the more information is obtained from the previous picture. In orders greater than four, however, the difference is hardly perceptible to the eye with the present screen technology.

- The functions used to calculate the coefficients are chosen in a suitable way. The condition is that  $\sum a_i = 1$  and  $\sum r_j = 1$ . It should be possible to find other functions as well, preferrably polynomials, using iteration, which would work acceptably.
- The coefficients are preferrably stored in a look-up table for fast retrieval for all possible values of f and g.

Thus, the present invention solves the problem with the prior art, because the 3x3 filters and the 4x4 filters do not have the low-pass characteristics of the 2x2 filter. It is also possible with the present invention to move a pixel an arbitrary subpixel distance. The invention is only limited by the claims below.

10

15

#### CLAIMS

1. Method of moving a pixel a subpixel distance, wherein the pixel value (q(n,k)) is calculated using the known motion vector (x+f, y+g) and pixel values (p(n', k')) located in the vicinity of the corresponding pixel in the previous picture, characterized in that

at least 3x3 pixels from the previous picture is used, that the pixel value is calculated as a sum of previous pixel values weighted with coefficients depending on the motion vector.

- 2. Method according to claim 1, characterized in that the coefficients are calculated as functions of the motion vector subpixel part (f, g).
- 3. Method according to claim 1, characterized in that the coefficients are calculated as polynomials of the motion vector subpixel parts (f, g).
  - 4. Method according to claim 1 or 2, characterized in that the coefficients and stored in a look-up table.
- 5. Method according to anyone of the preceding claims
  20 chraracterized in that 3x3 pixels from the previous
  picture are used, the value of the pixel being calculated as

$$q(n,k) = \sum_{i=-1}^{1} \sum_{j=-1}^{1} a_i r_j p(n+x+i,k+y+j)$$

25

where

the motion vector is (x+f, y+g); x and y are integers, -1/2 <  $f \le 1/2$  and  $-1/2 < g \le 1/2$ ,

p(n+x+i, k+y+j) are pixel values in the previous picture, 30 and the coefficients being calculated as

$$a_{-1} = \frac{-2f + 3f^2 - |f^3|}{4}$$

$$a_0 = \frac{2 - 3f^2 + |f^3|}{2}$$

$$a_1 = \frac{2f + 3f^2 - |f^3|}{4}$$

$$r_{-1} = \frac{-2g + 3g^2 - \left| g^3 \right|}{4}$$

$$r_0 = \frac{2 - 3g^2 + |g^3|}{2}$$

5

$$r_1 = \frac{2g + 3g^2 - |g^3|}{4}$$

6. Method according to claim 1-3, characterized in that 4x4 pixels from the previous picture are used, the pixel value being calculated as

$$q(n,k) = \sum_{i=-1}^{2} \sum_{j=-1}^{2} a_{i}r_{j}p(n+x+i,k+y+j)$$

15 where

the motion vector is (x+f, y+g); x and y are integers,  $0 \le f < 1$  and  $0 \le g < 1$ ,

p(n+x+i, k+y+j) is the pixel value in the previous picture and the coefficients being calculated as

20

$$a_{-1} = \frac{-7f + 12f^2 - 5f^3}{15}$$

$$a_0 = \frac{15 - 3f - 27f^2 + 15f^3}{15}$$

25

$$a_1 = \frac{12f + 18f^2 - 15f^3}{15}$$

$$a_2 = \frac{-2f - 3f^2 + 5f^3}{15}$$

$$r_{-1} = \frac{-7q + 12q^2 - 5q^3}{15}$$

$$r_0 = \frac{15 - 3q - 27q^2 + 15q^3}{15}$$

$$r_1 = \frac{12q + 18q^2 - 15q^3}{15}$$

$$r_2 = \frac{-2q - 3q^2 + 5q^3}{15}$$

1/1

$$(i, j)$$
  $(-1, -1)$   $(0, -1)$   $(1, -1)$ 

$$(0, -1)$$

$$(1, -1)$$

$$(-1, 0)$$



(-1, 1)

FIG. 1

$$(i, j)$$
  $(-1, -1)$   $(0, -1)$   $(1, -1)$   $(2, -1)$ 

$$(0, -1)$$

$$(1, -1)$$

$$(2, -1)$$

(1, 0)

(-1, 1)

(-1, 2)

FIG. 2

**SUBSTITUTE SHEET** 



International Application No PCT/SE 91/00530

I. CLASSIFICATIO	N OF SUBJECT MATTER (if several classi	fication symbols apply, indicate all) <sup>6</sup>				
According to Interna	tional Patent Classification (IPC) or to both t	lational Classification and IPC				
IPC5: G 06 F	15/66					
II. FIELDS SEARCH	IED					
W. 11025 5 5 W.	Minimum Docume	ntation Searched <sup>7</sup>				
Classification System Classification Symbols						
IPC5	G 06 F					
		r than Minimum Documentation s are Included in Fields Searched <sup>8</sup>				
<u> </u>	to the Extent that 30th occurrent	are microsey and reign Searches				
			J HT			
SE,DK,FI,NO c	classes as above					
III. DOCUMENTS CO	ONSIDERED TO BE RELEVANT9					
Category Citati	on of Document,11 with indication, where ap	propriate, of the relevant passages 12	Relevant to Claim No. <sup>13</sup>			
A EP, A2	, 0280316 (SONY CORPORATI	ON)	1-6			
31	August 1988,	-				
se	e the whole document					
		·				
		<del>-</del>				
		-				
* Special categories of cited documents: 10						
"A" document defining the general state of the art which is not considered to be of particular relevance or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention						
"E" earlier docume filing date	nt but published on or after the international	"X" document of particular relevance	e, the claimed invention			
"L" document which may throw doubts on priority claim(s) or involve an inventive step						
Citation or other special reason (as specified)  cannot be considered to involve an inventive step when the						
"O" document referring to an oral disclosure, use, exhibition or other means  "O" document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.						
'P' document published prior to the international filing date but later than the priority date claimed "&" document member of the same patent family						
IV. CERTIFICATION						
Date of the Actual Com	pletion of the International Search	Date of Mailing of this International Se	arch Report			
15th October	1991	1991 -11- 0 5				
International Searching	Authority	Signature of Authorized Officer				
ei national Searching	, comorny	The state of Manier and State of the State o	CO10.			
CHED	TOU DATENT OFFICE	JAN SILFVERLING	deferra			
2MED	ISH PATENT OFFICE '	OVIA STELACUETING				

# ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.PCT/SE 91/00530

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the Swedish Patent Office EDP file on 91-08-30 The Swedish Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication	Patent family		Publication	
	date	member(s)		date	
EP-A2- 0280316	88-08-31	AU-D- JP-A- JP-A- US-A- JP-A-	1212288 63208984 63208985 4874347 63213086	88-09-01 88-08-30 88-08-30 89-10-17 88-09-05	